### SM 1200 - SFM 1200

### SM 1200 break-out anti-panic system for mobile leaves

## Description and Characteristics of SM 1200 The break-out anti-panic system SM 1200 consists of: • Leaf fixing profile • Upper and lower brackets • Leaf guide profile • Installation accessories • Mobile leaf version (right or left) • Suitable for any commercial frame with internal dimensions 30x30 mm • Suitable for automations 930 SF - 930 SFA

| Use                  |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |
|----------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|
| Leaf max length (mm) | 500 | 550 | 600 | 650 | 700 | 750 | 800 | 850 | 900 | 950 | 1000 | 1050 | 1100 | 1150 | 1200 |
| Leaf max weight (kg) | 100 | 100 | 95  | 95  | 90  | 90  | 85  | 85  | 80  | 80  | 75   | 75   | 75   | 70   | 70   |

### SFM 1200 break-out anti-panic system for mobile and semi-fixed leaves

# Description and Characteristics of SFM 1200 The break-out anti-panic system SFM 1200 consists of: • Leaf fixing profile • Upper and lower brackets • Leaf guide profile • Installation accessories • Mobile leaf version (right or left) • Suitable for any commercial frame with internal dimensions 30x30 mm • Suitable for automations 930 SF - 930 SFA

| Use                  |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |
|----------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|
| Leaf max length (mm) | 500 | 550 | 600 | 650 | 700 | 750 | 800 | 850 | 900 | 950 | 1000 | 1050 | 1100 | 1150 | 1200 |
| Leaf max weight (kg) | 100 | 100 | 95  | 95  | 90  | 90  | 85  | 85  | 80  | 80  | 75   | 75   | 75   | 70   | 70   |