



keyboard device and decoding system



Characteristics

METAL DIGIKEY

- Flush-mounted or column installation
- 24 Vdc power supply
- Anti-break-in electronic protection
- Indicator-light and buzzer confirming recognition
- Reset push-button
- Max number of connectable decoders: 100
- IP 55 protection class

DECODER DS

- Decoding card (relay output) for piloting FAAC control board and/or auxiliary controls
- Connector and/or terminal connection
- 12 - 24 Vdc /12 - 24 Vac power supply
- 12-bit binary code (4.096 combinations)
- Max distance of Metal Digikey/Decoder: 100 m
- Operating ambient temperature -20°C +55°C



magnetic card reader and decoding system



Specifications

DIGICARD

- Flush-mounted or column installation
- 12 - 24 Vdc/14 Vac power supply
- Anti-break-in electronic protection
- Indicator-light and buzzer confirming recognition
- Reset push-button
- Max number of connectable decoders: 100
- IP 55 protection class

DECODER DS

- Decoding card (relay output) for piloting FAAC control board and/or auxiliary controls
- Connector and/or terminal connection
- 12 - 24 Vdc/12 - 24 Vac power supply
- 12-bit binary code (4.096 combinations)
- Max distance of Metal Digikey/Decoder: 100 m
- Operating ambient temperature -20°C +55°C