

enclosures



Mod. E



Mod. L/LM

Characteristics of Mod. L-LM

- | | |
|--|--|
| <ul style="list-style-type: none"> • IP 55 protection class • Wall- or flush-mounting • Designed for securing to DIN guide • Fuse-holder • Designed for installation of door locking switch | <ul style="list-style-type: none"> • Removable hinges for right or left opening • Seats for capacitor supports • Lock with standard triangular key • Coded-key lock (optional) |
|--|--|

Characteristics of Mod. L

- | | |
|--|--|
| <ul style="list-style-type: none"> • Dimensions (lxhxd): 213 x 270 x 118 (mm) • N. 3 closing plugs for Ø 29 hole | <ul style="list-style-type: none"> • N. 2 knockout holes Ø 19 |
|--|--|

Characteristics of Mod. LM

- | | |
|--|--|
| <ul style="list-style-type: none"> • Dimensions (lxhxd): 246 x 353 x 142 (mm) • N. 2 closing plugs for Ø 29 hole | <ul style="list-style-type: none"> • N. 2 knockout holes Ø 29 • N. 2 knockout holes Ø 19 |
|--|--|

Characteristics of Mod. E

- | | |
|--|---|
| <ul style="list-style-type: none"> • IP 55 protection class • Wall- or flush-mounting • Designed for securing to DIN guide • Fuse-holder | <ul style="list-style-type: none"> • Designed for installation of door locking switch • Cover closing by 4 self-tapping screws • Seats for capacitor supports • Dimensions (lxhxd): 204 x 265 x 85 (mm) |
|--|---|